Alabama Energy Code home buyers checklist

Is your new home energy-efficient? Before you buy, get the facts. Use this checklist to determine if construction meets Alabama's new residential energy code.

Lighting	Air Sealing
At least half of the home's lighting fixtures are high efficiency lights	All holes between floors and through walls have been sealed with caulk or foam
Ducts	Windows
In Attic: Ceiling and walls are insulated, OR:	Window Skylight Solar Heat U-Factor U-Factor Gain Coefficient
Ducts are sealed and insulated to a value of R-6 Effective July 1, 2013, ducts must be sealed and insulated to a value of R-8	Baldwin & Mobile 0.65 0.75 0.30 Counties
Whole House:	All Other Counties 0.50 0.65 0.30
All ducts are sealed with mastic, a type of caulk (Duct tape is not sufficient) Insulation	Tests
Insulation	Tests
Crawl space walls and/or floor above are properly insulated	The blower door test resulted in a score of seven air changers per hour (ACH) or less (if applicable)
Attic access hatch or door is weather-stripped and insulated	The builder tested the ducts for air leakage
Fireplace	Energy Certificate
The fireplace doors are sealed with gaskets	(Voluntary) Energy Certificate located on circuit breaker box is completed and signed Please see reverse side for an example and more details.
Alternative C	ompliance Path

Alternative Compliance Path

If these requirements are not met, ask the builder for documentation showing the home meets minimum standards for energy consumption.

You have a right to an affordable, energy-efficient home.

Make sure your new home checks out!





For more information and to learn how to verify whether your home meets national standards, visit www.adeca.alabama.gov/C0/codes

The consumer education campaign is made possible by the combined efforts of the following organizations: Alabama Department of Economic and Community Affairs, U.S. Department of Energy, and Building Codes Assistance Project.

Sample Energy Certificate

Alabama Homes

Counties other than Mobile and Baldwin



This energy certificate from the 2009 RECA illustrates the energy efficiency standards which are required in every new home in Alabama. This sample form has been completed with the **minimum** standards for each building element in the home, meaning that the certificate in new homes should meet these standards or better. Look for this certificate in or near the home's circuit breaker box or electric panel box. Make sure that it has been signed by the builder and identifies the other contractors.

If you have any questions about what is reported on the certificate, ask your builder or your local building permits office.

U-factors

These are the requirements for the insulation value of a home's windows, doors, and skylights. U-values on the home's energy certificate should be **less than or equal to** those shown in the certificate below.

R-values

These are the minimum requirements allowed for the home's insulation in order to meet the code. R-values on the form should be **greater** than or equal to those shown here.

Heating and Cooling (HVAC)

The way heating and cooling systems are rated and the minimum levels for efficiency depend on the type installed, and fuel used. These abbreviations: SEER, AFUE, and HSPF indicate efficiency. The higher the rating, the more efficient the heating or cooling system is. Use the chart below to determine the minimum rating allowed for each system.

type	min rating
air conditioner	SEER-13
electric furnace	AFUE: 78%
electric boiler	AFUE: 80%
gas boiler	AFUE: 75%
heat pump	HSPF: 7.7

2009 IRC Energy Certificate **Counties other than Mobile and Baldwin Compliance Method** Date 6-30-11 PRESCRIPTIVE R-value Insulation Ceiling/Roof 30 Walls 13 Floors 19 Ducts **Basement Walls U-factor Window and Door Ratings** Windows 0.50 0.50 Doors **HVAC Equipment** Type Rating GAS BOILER 752 AFUE Heating SEER-13 Air Conditioning FORCED AIR **Water Heating** Type EF value Water Heater 50 GAL, GAS 0.60 General Contractor: Rts CONTRACTORS Insulation Contractor: CMITH & SON Form Completed By:

Water Heater

The minimum efficiency factor (EF) for water heaters depends on the size and fuel type used. The higher the number, the more efficient the water heater is.

Minimum EFs for Water Heaters

size	gas	electric
30 gal	0.63	0.95
40 gal	0.62	0.95
50 gal	0.60	0.95
65 gal	0.75	1.98
75 gal	0.74	1.97

*"5/13" means R-10 continuous insulated sheathing on the interior or exterior of the home (sealed at joints) or R-13 cavity insulation at the interior of the basement wall.